

Description

The SEG-X1 Smart Gateway acts as a central platform for your smart home system. It allows you to add ZigBee devices into the system and to be controlled by the mobile app, while at the same time provide more stable connection through Ethernet.

Main Features

- ZigBee HA1.2 compliant
- ZigBee coordinator of the home area network
- Powerful CPU for complicated calculation
- Real time and efficiently interoperability with cloud server

API for Third-party Integration

OWON offers open Server API (Application Programming Interface) and Gateway API to facilitate the flexible integration between the Gateway and the third party Cloud Server. The users can integrate the Gateway with a designated Cloud Server / Mobile App following the Gateway API.

Main Specifications

Physical Specifications	
CPU	• MIPS, 200MHz
Flash Rom	• 2MB
Data Interface	• Micro USB port
SPI Flash	• 16MB
Ethernet	• 100M bps • Auto MDIX
RF Characteristics	 Operating frequency: 2.4GHz Internal PCB Antenna Range outdoor/indoor: 100m/30m (open area)
Power Supply	• 5V DC • Rated power consumption: 1W
LEDs	Power, ZigBee, Ethernet, Bluetooth
Dimensions	• 91.5(W) x 133 (L) x 28.2(H) mm
Weight	• 103 g
Mounting Type	 Direct Plug-in Plug Type: US, EU, UK, AU

Software	
WAN Protocols	 IP Addressing: DHCP, Static IP Data Porting: TCP/IP, TCP, UDP Security Modes: SSL
ZigBee Profile	Home Automation Profile
Downlink Commands	 Data format: JSON Gateway Operation Command HAN Control Command
Uplink Messages	 Data format: JSON Home Area Network information
Security	Authentication Password protection on mobile apps Server/gateway interface authentication ZigBee Security Preconfigured Link Key Certicom Implicit Certificate Authentication Certificate-Based Key Exchange (CBKE) Elliptic Curve Cryptography (ECC)