




Products

– Control & Lightings

SLC605

ZigBee Wall Switch (US)



Description

The In-wall switch allows you to remotely control your lighting or even set schedules for automatic switching. The switch can also be linked with a ZigBee-enabled LED bulb so that you can remotely adjust the level of brightness manually using the wall switch.

Main Features

- ZigBee HA 1.2 compliant
- Remote on/off control
- Extends the range and strengthens ZigBee network communication
- Enables scheduling for automatic switching

Main Specifications

Wireless Connectivity	
ZigBee	<ul style="list-style-type: none">• 2.4GHz IEEE 802.15.4
ZigBee Profile	<ul style="list-style-type: none">• ZigBee HA 1.2
RF Characteristics	<ul style="list-style-type: none">• Operating frequency: 2.4GHz• Range outdoor/indoor: 100m / 30m• Internal PCB Antenna
Physical Specifications	
Operating Voltage	<ul style="list-style-type: none">• 100~125 Vac 50/60 Hz
Power consumption	<ul style="list-style-type: none">• < 0.7 W
Max. Load Current	<ul style="list-style-type: none">• 10 A
Operating environment	<ul style="list-style-type: none">• Temperature: -20 °C ~+55 °C• Humidity: ≤ 90% non-condensing
Dimension	<ul style="list-style-type: none">• 107 x 50 x 41 mm
Weight	<ul style="list-style-type: none">• 115 g
Mounting Type	<ul style="list-style-type: none">• In- wall mounting• US standard
Certificate	<ul style="list-style-type: none">• ROSH/UL/ETL