





## Products

### – Control & Lightings

SLC628

In-Wall Switch



## Description

The In-wall Touch Switch allows you to remotely control your lighting or even apply schedules for automatic switching from the mobile app.

## Main Features

- ZigBee 3.0 compliant
- Works with any standard ZigBee Hub
- Remote on/off control using your smartphone
- Set schedules to automatically power on and off as needed
- 1/2/3/4 gang is available for selection

## Main Specifications

Wireless Connectivity	
ZigBee	<ul style="list-style-type: none"><li>• 2.4GHz IEEE 802.15.4</li></ul>
ZigBee Profile	<ul style="list-style-type: none"><li>• ZigBee 3.0</li></ul>
RF Characteristics	<ul style="list-style-type: none"><li>• Operating frequency: 2.4GHz</li><li>• Range outdoor/indoor: 100m / 30m</li><li>• Internal PCB Antenna</li></ul>
Physical Specifications	
Button	<ul style="list-style-type: none"><li>• Touch Screen</li></ul>
Operating Voltage	<ul style="list-style-type: none"><li>• 100~240 Vac 50/60 Hz</li></ul>
Power consumption	<ul style="list-style-type: none"><li>• &lt; 1 W</li></ul>
Max. Load Current	Each gang: <ul style="list-style-type: none"><li>• &lt; 700W Resistive</li><li>• &lt; 200W Inductive</li></ul>
Operating environment	<ul style="list-style-type: none"><li>• Temperature: -20 °C ~+55 °C</li><li>• Humidity: ≤ 90% non-condensing</li></ul>
Dimension	<ul style="list-style-type: none"><li>• 86 x 86 x 47 mm</li><li>• In-wall size: 75x 48 x 28 mm</li><li>• Thickness of the front panel: 9 mm</li></ul>
Weight	<ul style="list-style-type: none"><li>• 114 g</li></ul>
Mounting Type	<ul style="list-style-type: none"><li>• In- wall mounting</li><li>• EU standard or CN standard</li></ul>
Certificate	<ul style="list-style-type: none"><li>• EU: ROHS</li><li>• CN: CE, ROHS</li></ul>